



THE POWER OF CLEAN EFFICIENT LIGHT



4-ft., 4-LAMP T8 ENCLOSED & GASKETED FIXTURE

The EG14-4T8-FG-HB is designed for applications that include general lamination, rough service commercial, industrial, and retail environments. This fixture is ideal for any non-hazardous location application that requires a wet location or dust proof fixture. The EG14-4T8-FG-HB is a “made-for-purpose” enclosed and gasketed fixture (not a strip installed into a housing) constructed of Glass Reinforced Polyester (housing) and Acrylic (diffuser) material.

INSTANT START ELECTRONIC BALLAST

The EG14-4T8-FG-HB comes complete with energy efficient instant start electronic ballasts. The ballasts are Class P type (thermal protection), Class A sound rated and minimum starting temperature of -20/-29 (F/C).

LISTING

The EG14-4T8-FG-HB is certified cETLus for installations in the U.S. or Canada. The fixture is certified to CSA C22.2 No.250.0 and conforms to UL 1598.

EG14-4T8-FG-HB (Fiberglass) Linear Fluorescent Enclosed & Gasketed Fixture 4-ft., 4-Lamp, T8 (32-watt)

FEATURES & BENEFITS

- Diffuser is clear acrylic material
- Housing is fiberglass material.
- Poured-in silicon gasket between housing and diffuser.
- Stainless steel hinged latches hold diffuser to housing.
- Internal metal ballast/gear tray and reflector is painted with white enamel.
- Rotary lock lamp holders for positive lamp contact.
- IP67 Rated.
- Quick disconnect is included for ease of installation.
- Engineered for use with T8, 32W lamps (not included)

FIXTURE DIMENSIONS:

<u>Length</u>	<u>Width</u>	<u>Depth</u>	<u>Weight</u>
51-in	17.7-in	6.7-in	20-lbs

All dimensions are inches.

Specifications subject to change without notice.

PHOTOMETRIC DATA: Available upon request