



**THE POWER OF CLEAN EFFICIENT LIGHT**



#### **2-ft., 2 -LAMP T8 HAZARDOUS LOCATION FIXTURE**

The HLF1 is available as a T8 lighting fixture intended for the following hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D

Designed for applications requiring corrosion resistant fixtures. Excellent for marine wet and damp locations. Inside of fixture is drip-proof. Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

Housing is non-metallic glass reinforced polyester. Gasket is poured in-place. Latches are stainless steel locking type. Diffuser is high impact acrylic. End mounting brackets are standard with fixture.

#### **ELECTRONIC BALLAST**

HLF1 models come complete with energy efficient, 120-277 multi-volt, electronic, automatic resetting, instant start (T8) ballasts. The ballasts are Class P type (thermal protection), Class A sound rated and minimum starting temperature of -20/-29 (F/C).

#### **LISTING**

The HLF1 fixture is certified to the following:  
UL 1598-A – Outdoor Marine Type (salt water)  
UL 844 – Class I, Div 2, A,B,C,D  
Meets Coast Guard Specifications

## **HLF1-2-2-26-UNV-T8**

**Non-Metallic**  
**Linear Fluorescent Hazardous Location**  
**2-ft., 2-Lamp, T8 (17-watt)**

#### **FEATURES & BENEFITS**

- F17T8/850 lamps are supplied with the fixture as a standard feature.
- Fixture is supplied with stainless steel mounting brackets as standard equipment.
- Fixture housing is constructed of non-metallic glass reinforced polyester.
- Silicon gasket is poured in-place.
- Diffuser is high impact acrylic.
- Fixture can be surface mounted or suspended.
- Fixture is warranted for one year from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.
- Approximate Fixture Dimensions &Weights

#### **2-ft., 2-lamp**

Length: 28-inches

Width: 8.4-inches

Height: 7-inches