



THE POWER OF CLEAN EFFICIENT LIGHT



**4-ft., 2/3/4 -LAMP T8 OR T5HO
HAZARDOUS LOCATION FIXTURE**

The HLF7 is available as a T8 or T5HO lighting fixture intended for the following hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D
- Class II, Div. 2

Designed for applications requiring metallic fixtures. Excellent for wet and damp locations. Typical applications include Chemical Plants, Water Treatment, Paper Mills, Machining Areas and Coal and Dust Storage Areas.

ELECTRONIC BALLAST

HLF7 models come complete with energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) or instant start (T8) ballasts. The ballasts are Class P type (thermal protection), Class A sound rated and minimum starting temperature of -20/-29 (F/C).

LISTING

The HLF7 fixture is certified to the following:

- UL 844 – Class I, Div. 2, A,B,C,D and Class II, Div. 2

**HLF7-4-2-26-UNV-T8
HLF7-4-3-26-UNV-T8
HLF7-4-4-26-UNV-T8
HLF7-4-2-46-UNV-T5HO
HLF7-4-3-46-UNV-T5HO
HLF7-4-4-46-UNV-T5HO**

Linear Fluorescent Hazardous Location

**2-Lamp, T8 (32-watt)
3-Lamp, T8 (32-watt)
4-Lamp, T8 (32-watt)
2-Lamp, T5HO (54-watt)
3-Lamp, T5HO (54-watt)
4-Lamp, T5HO (54-watt)**

FEATURES & BENEFITS

- F32T8/850 or F54T5/HO/850 lamps are supplied with the fixture as a standard feature.
- Front access fixture for hazardous locations
- Hinged front door frame.
- Hinged ballast tray.
- 18 Ga. steel white housing .
- Top and side hubs
- Spring loaded lamp holders
- 3/16" tempered glass lens
- Zinc latches