

General Description and Usage

The L-CP Series is an LED Canopy light for outdoor use applications. This Canopy light is available in 40-watt, 5450 lumen or 60-watt 8000 lumen configurations. The LED Canopy light is an energy efficient light source that lasts up to 60% longer than standard lighting. The fixture is designed for security, garage parking, pathway, warehouse, entrances/exits, and perimeter lighting applications.

Construction

Housing is constructed rugged-cast aluminum housing with bronze polyester powder coat for lasting durability. The fixture is rust and corrosion proof. Endures extreme climate changes without cracking or peeling. Fully sealed to be dirt and bug proof. Multiple knockouts for mounting convenience.

Electrical

Fixtures are standard for use in 120-277 volt environments. Long-life LEDs, coupled with high efficiency drivers, provide superior level and quality of illumination for extended service life. Fixture life is 50,000 hors L70 rated life.

Listings

UL certified to U.S. and Canadian standards. DesignLights Consortium® (DLC) qualified product.

Warranty

5 year limited warranty.



Note: Actual performance may differ as a result of enduser environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

L-CP-S-40 L-CP-L-60



L-CP SERIES

Features

- Capable of replacing up to 250W metal halide luminaire
- 120-277V universal voltage
- Color temperature 5000K with minimum CRI 70
- Glare free, uniform illumination
- Multiple knockouts for mounting convenience

Available configurations

- L-CP-S 40 Watt, 5450 Lumens
- L-CP-L 70 Watt, 8000 Lumens

Dimensions

L-CP-S-40

Length - 9.5" Width - 9.5" Height - 3.0"

L-CP-L-60

Length - 9.5" Width - 9.5" Height - 3.0"