

# **General Description and Usage**

The LW-4-40 Series fixture is a versatile utility based, traditionally styled LED wraparound series which offers broad range of uses including commercial, schools, institutional, retail and residential applications. This High quality luminaire series utilizes the latest solid state LED lighting and advanced electronic driver technology which provides optima lighting performance in maximizing energy savings. The LW-4-40 is designed to provide long service life eliminating re-lamping issues and minimizing maintenance common with traditional fluorescents.

Housing consist of die formed cold rolled steel housing with a white powder coat finish. Acrylic, high performance, prismatic acrylic lens. Ends complete with knock out for row mounting.

#### **Electrical**

Fixtures are standard for use in 120-277 volt environments. Long-life LEDs, coupled with high-efficiency drivers, provide superior level and quality of illumination for extended service life. Fixture life is 50,000 hours.

#### Listings

ETL certified to U.S. and Canadian standards. DLC Certified.

#### Warranty

5 year limited warranty.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.



# LED WRAP AROUND 4-FT 40 WATT



## LW-4-40

## **LED Benefits**

- Available in a 4-ft., length
- Steel housing with white powder coat finish
- Diffusing prismatic acrylic lens
- 120V input
- Up to 110 lumens per watt
- Color temperature 4000K with minimum CRI80
- 50,000 hours L70 rated life
- Designed to meet Energy Star

## **Available configurations**

#### LW-4-40

LED Wraparound 4-ft., 40 Watt

#### **Dimensions**

4-ft. fixture - 48" X 7.5" X 2.5"



# **Fixture Dimensions**



# **Light Distribution**

