



General Description and Usage

The LWP-M Series LED wall pack family combines traditional wall pack design with high-output LED light engines to provide an energy-efficient, low maintenance LED wall pack suitable for replacing up to 400W MH fixtures. The traditional shape helps maintain building aesthetics when replacing only a portion of your building's wall packs. The LWP-S LED wall pack series is ideal for outdoor applications such as carports, loading areas, driveways and parking areas. The LWP-M is manufactured with a cast-aluminum housing with a dark bronze polyester powder coating for durability. The fixture door is hinged on the side to allow the door to swing out of the way during installation and service. Castings are sealed with a one-piece gasket to keep dust and water from entering the fixture. The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

Electrical

The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

Optical

Prismatic glass lens is designed for superior lighting distribution, uniformity and fixture spacing.

Listings

UL certified to U.S. and Canadian standards. Design Lights Consortium® (DLC) qualified product.

Warranty

5 year limited warranty.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.



LED FULL CUT OFF WALL PACK



LWP-FCO-M SERIES

LED Benefits

- Environment friendly - No mercury or lead
- 60% energy savings compared to fluorescent luminaires
- Maintenance free operation
- Last up to 20 times longer than conventional lamps
- Up to 95 lumens per watt
- Direct replacement for traditional incandescent.

Available configurations

LWP-FCO-M-45W
Full Cutoff 45-watt

LWP-FCO-M-70W
Full Cutoff 70-watt

Dimensions

14.21" x 8.78" x 9.25"