

LED WALL PACKS FULL CUTOFF SMALL

General Description and Usage

The LWP-FCO-S Series LED wall pack family is ideal for commercial and industrial wall-mounted applications where traditional metal halide fixtures would typically be used. The LWP-FCO-S is versatile and efficient. The fixture head can be rotated to light the exact area required and the LWP-FCO-S is designed to replace up to 250W metal halide while saving up to 85% in energy costs. It employs the latest generation of LEDs for a wall pack luminaire that converts to much more. The LWP-FCO-S is ideal for outdoor applications such as building perimeters, loading areas, driveways and sign and building floodlighting.

The LWP-FCO-S is available in four light levels, 3600, 5200, 8800 and 10500 lumen output. The LWP-FCO-S series fixtures offer a versatile look that complements many applications.

The LWP-FCO-S is manufactured with a cast-aluminum housing with a dark bronze polyester powder coating for durability. Castings are sealed with a one-piece gasket to keep dust and water from entering the fixture. The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

Electrical

The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

Optical

Type III polycarbonate lens with UV stabilizers is designed for superior lighting distribution, uniformity and fixture spacing.

Warranty

5-year limited warranty.

Note:

Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.



LWP-FCO-S-27/40/67/80

Listings

- UL certified to U.S. and Canadian standards.
- DesignLights Consortium® (DLC) qualified product

LED Benefits

- Environment friendly - No mercury or lead
- Up to 60% energy saving compared to fluorescent luminaires
- Maintenance free operation, last up to 20 times longer than conventional lamps
- Direct replacement for traditional T8 fluorescent

Available configurations

LWP-FCO-S-27w - 27-watt / 3600 lm

LWP-FCO-S-40w - 30-watt / 5200 lm

LWP-FCO-S-67w - 67-watt / 8800 lm

LWP-FCO-S-80w - 80-watt / 10500 lm

Dimensions

8.9" x 6.8 "x 4.1"

