# † Truex Lighting

## **General Description and Usage**

The LWP-S Series LED wall pack family combines traditional wall pack design with high-output LED light engines to provide an energy-efficient, low maintenance LED wall pack suitable for replacing up to 750-W MH fixtures. The traditional shape helps maintain building aesthetics when replacing only a portion of your building's wall packs. The LWP-S LED wall pack series is ideal for outdoor applications such as carports, loading areas, driveways and parking areas.

The LWP-S is manufactured with a cast-aluminum housing with a dark bronze polyester powder coating for durability. The fixture door is hinged on the side to allow the door to swing out of the way during installation and service. Castings are sealed with a one-piece gasket to keep dust and water from entering the fixture. The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

## **Electrical**

The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

## Optical

Prismatic polycarbonate, UV stabilized lens is designed for superior lighting distribution, uniformity and fixture spacing.

## Listings

UL certified to U.S. and Canadian standards. DesignLights Consortium® (DLC) qualified product.

### Warrantv

5-year limited warranty.

## Note:

Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

# LED WALL PACKS



LWP-S- SERIES

## **LED Benefits**

- Environment friendly No mercury or lead
- Up to 60% energy saving compared to fluorescent luminaires
- Maintenance free operation, last up to 20 times longer than conventional lamps
- Direct replacement for traditional T8 fluorescent

## **Available Configurations**

- **LWP-S-45W** 45-watt / 5300 lm
- LWP-S-70W 70-watt / 8100 lm

### **Dimensions**

14.20" x 9.25 "x 7.2"

See complete product specifications below



# **Fixture Performance**

FIXTURE WATTS	LUMENS	LUMENS/WATT	VOLTAGE
45	5300	118	120-277
70	8100	116	120-277

# **Fixture Dimensions**





