



THE POWER OF CLEAN EFFICIENT LIGHT



4-ft., 2 -LAMP T8 HAZARDOUS LOCATION FIXTURE

The HLF1 is available as a T8 or T5HO lighting fixture intended for the following hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D

Designed for applications requiring corrosion resistant fixtures. Excellent for marine wet and damp locations. Inside of fixture is drip-proof. Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

Housing is non-metallic glass reinforced polyester. Gasket is poured in-place. Latches are stainless steel locking type. Diffuser is high impact acrylic. End mounting brackets are standard with fixture.

ELECTRONIC BALLAST

HLF1 models come complete with energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) or instant start (T8) ballasts. The ballasts are Class P type (thermal protection), Class A sound rated and minimum starting temperature of -20/-29 (F/C).

LISTING

The HLF1 fixture is certified to the following:
UL 1598-A – Outdoor Marine Type (salt water)
UL 844 – Class I, Div 2, A,B,C,D
Meets Coast Guard Specifications

HLF1-4-2-26-UNV-T8 HLF1-4-2-46-UNV-T5HO

**Non-Metallic
Linear Fluorescent Hazardous Location
2-Lamp, T8 (32-watt)
2-Lamp, T5HO (54-watt)**

FEATURES & BENEFITS

- F32T8/850 or F54T5/HO/850 lamps are supplied with the fixture as a standard feature.
- Fixture housing is constructed of non-metallic glass reinforced polyester.
- Silicon gasket is poured in-place.
- Diffuser is high impact acrylic.
- Fixture can be surface mounted or suspended.
- Fixture is warranted for one year from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.
- Approximate Fixture Dimensions &Weights

4-ft., 2-lamp

Length: 52-inches

Width: 8.4-inches

Height: 7-inches

FIXTURE DIMENSIONS:

