



THE POWER OF CLEAN EFFICIENT LIGHT



4-ft., 2 -LAMP T8 HAZARDOUS LOCATION FIXTURE

The HLF3 is available as a T8 or T5HO lighting fixture intended for the following hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D

Designed for applications requiring metallic fixtures. Excellent for marine wet and damp locations. Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

Housing is extruded aluminum with clear diffuser/lens. End mounting brackets are standard with the fixture

ELECTRONIC BALLAST

HLF1 models come complete with energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) or instant start (T8) ballasts. The ballasts are Class P type (thermal protection), Class A sound rated and minimum starting temperature of -20/-29 (F/C).

LISTING

The HLF3 fixture is certified to the following:

- UL 595 – Outdoor Marine Type (salt water)
- UL 844 – Class I, Div 2, A,B,C,D
- Meets Coast Guard Specifications

HLF3-4-2-26-UNV-T8

HLF3-4-2-46-UNV-T5HO

Extruded Aluminum

Linear Fluorescent Hazardous Location

2-Lamp, T8 (32-watt)

2-Lamp, T5HO (54-watt)

FEATURES & BENEFITS

- F32T8/850 or F54T5/HO/850 lamps are supplied with the fixture as a standard feature.
- Fixture housing is constructed of extruded aluminum.
- End mounting brackets are standard with fixture.
- Diffuser/lens is clear.
- Fixture can be surface mounted or suspended.
- Fixture is warranted for one year from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.
- See page two of spec sheet for fixture dimensions with and without mounting brackets.



HLF3-4-2-26-UNV-T8
HLF3-4-2-46-UNV-T5HO

FIXTURE DIMENSIONS:

- Dim. A - 49 ³/₄"
- Dim. B - 47"
- Dim. C - 4 ³/₄"
- Dim. D - 7"
- Dim. E - 6 ¹/₈"
- Dim. F - 6 ¹/₈"
- (Shipping Weight: 33 lbs)

