

## LED WALL PACKS FULL CUTOFF

### General Description and Usage

The LWP-FCO-L Series LED wall pack family is ideal for commercial and industrial wall-mounted applications where traditional metal halide fixtures would typically be used. The LWP-FCO-L is available in four light levels, 4900, 7350, 9500 and 14000 lumen output. This LED fixture can provide up to 80% energy savings over the traditional metal halide equivalent and can be used to replace up to 400 watt metal halide fixtures. The LWP-FCO-L series fixtures offer traditional square forms with square edges for a versatile look that complements many applications.

The LWP-FCO-L LED wall pack series is ideal for outdoor applications such as building wall wash and security lighting. The LWP-FCO-L is manufactured with a cast-aluminum housing with a dark bronze polyester powder coating for durability. Castings are sealed with a one-piece gasket to keep dust and water from entering the fixture. The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

### Electrical

The universal voltage driver operates on any line voltage from 120-277V (50/60Hz). Rated for outdoor installations, -25°C minimum ambient.

### Optical

Type III polycarbonate lens with UV stabilizers is designed for superior lighting distribution, uniformity and fixture spacing.

### Warranty

5-year limited warranty.

### Note:

Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.



### LWP-FCO-L SERIES

#### Listings

- UL certified to U.S. and Canadian standards.
- DesignLights Consortium® (DLC) qualified product
- Dark Sky compliant product

#### LED Benefits

- Environment friendly - No mercury or lead
- Up to 60% energy saving compared to fluorescent luminaires
- Maintenance free operation, last up to 20 times longer than conventional lamps
- Direct replacement for traditional T8 fluorescent

#### Available Configurations

- **LWP-FCO-L-45** - 45-watt / 4900 lm
- **LWP-FCO-L-70** - 70-watt / 7350 lm
- **LWP-FCO-L-90** - 90-watt / 9500 lm
- **LWP-FCO-L-135** - 135-watt / 14000 lm

#### Dimensions

19" x 11" x 10.5"