

SSLED-HB Series High Bay Fixture

This 165W high bay fixture delivers high lumen output with exceptional 82+CRI light while achieving 21,285 lumen output. The SSLED-HB-160-50-UNV is our new LED High Bay fixture for a wide variety of appli-cations and mounting heights. Precision-designed op-tics, multiple distributions, and a choice of lumen out-puts and color temperatures make the energy-efficient SSLED-HB is the ideal solution for industrial, commercial and other high bay applications. This fixture is designed to replace either metal halide or fluorescent high bay fixtures.

Electrical

Long-life LED system coupled with electronic driver delivers optimal performance. LED's available in 82+ CRI, 5000k. Projected LED life is greater than 50,000 hours. Fixture is cULus listed. Electronic drivers are available for 120- 277V applications.

Mounting

The LED High Bay can be suspended from the ceiling by either air craft cable hanging kit or chain with "V" hooks or it can be mounted on the ceiling directly.

Optics

Precision designed optics deliver even illumination. General and aisle distribution ensures superior performance to key areas within an application.



LED High Bay, 165-Watt / 21,285 lumens



SSLED-HB-165-50-UNV

Features

- Die-formed 20-gauge cold-rolled steel housing
- Frosted Acrylic Lens
- 5-year warranty
- Dimmable driver
- Installation includes aisle ways, warehouses, and industrial type environments.
- Removable lens with a two set screw option

Configuration

SS-HB-160-50-UNV

2-ft. Linear LED High Bay / 165-watt / 21,285 lm / 5000k color temperature

Dimensions

23.8"L x 12.6"W x 3.62"H